



EVEN OUR SMALLEST TRACTOR STILL PACKS A BIG PUNCH.





10

SERIES



TRACTOR MODEL	1022	1025
TYPE	3 CYLINDER, WATER COOLED, DIESEL	3 CYLINDER, WATER COOLED, DIESEL
ENGINE HP @ RPM (KW)	21.5 (16)	24.6 (18.4)
DISPLACEMENT (IN) (KW)	60.6 (993)	77.3 (1,267)
NUMBER OF CYLINDERS	3	3
FUEL TANK (GAL) (L)	6.6 (25)	5.8 (22)
DRIVE TRAIN		
TRANSMISSION	HST	HST
NUMBER OF SPEEDS	2 RANGE	2 RANGE
CLUTCH	NO	NO
BRAKES	WET, MULTI-DISC	WET, MULTI-DISC
PTO		
TYPE	INDEPENDENT	INDEPENDENT
REAR(MID) PTO SPEED	540 (2,500)	540 (2,000)
PTO HP (KW)	15.4 (11.3)	18.8 (14.0)
HYDRAULICS		
TYPE	POWER ASSISTED HYDROSTATIC	POWER ASSISTED HYDROSTATIC
TOTAL HYDRAULIC FLOW (POWER STEERING+IMPLEMENT)	6.3 (2.1+4.2) / 23.8 (8+15.8)	7.0 (2.8+4.2) / 25.7 (10.5+15.8)
3-POINT HITCH	CAT I	CAT I
REAR REMOTE VALVE	OPTIONAL (UP TO 1)	OPTIONAL (UP TO 1)
3POINT HITCH LIFT CAPACITY @24" BEHIND LIFT POINT	679 (308)	1,101 (499)
ELECTRICAL		
BATTERY	12 V, 500 CCA	12 V, 500 CCA
ALTERNATOR	12 V, 40 A	12 V, 40 A
DIMENSIONS		
OVERALL LENGTH IN(MM)	94.2 (2,394)	104 (2,633)
OVERALL WIDTH IN(MM)	44.5 (1,130)	45.8 (1,164)
OVERALL HEIGHT IN(MM)	86.6 (2,200)	91.3 (2,320)
WHEELBASE IN(MM)	53.1 (1,350)	57.5 (1,460)
MINIMUM GROUND CLEARANCE IN(MM)	8.3 (210)	9.5 (240)
TURNING RADIUS	45°	45°
WEIGHT LBS(KG)	1,433 (650)	1,610 (730)
WHEELS & TIRES		
IND (FRONT)	18X8.50-10	20X8.00-10
IND (REAR)	26X12.00-12	27X12.50-15
LOADER MODEL		
STANDARD BUCKET SIZE (IN)	BBL100 50"	BBL105 50"
MAXIMUM LIFT HEIGHT (IN)	71.3"	71.3"
DIG DEPTH (IN)	4.0"	4.6"
LIFT CAPACITY TO FULL HEIGHT AT PIVOT PIN (LBS)	617	617
BREAKOUT FORCE (LBS)	1,253	1,235
SHIPPING WEIGHT (LBS)	438	573
BACKHOE MODEL		
STANDARD BUCKET SIZE (IN)	BBH100 12"	BBH105 12"
TYPE	SUBFRAME-MOUNTED, QUICK ATTACH	SUBFRAME-MOUNTED, QUICK ATTACH
MAXIMUM DIG DEPTH (IN)	66"	76"
DIG FORCE BUCKET (LBS)	1,975	2,020
SHIPPING WEIGHT (LBS)	747	816



SPECIFICATIONS SUBJECT TO CHANGE

YOUR EXCLUSIVE DEALER: